

# TPF 5000

## Shrink and seal unit



- exclusively available
- exceptional price
- unsurpassable results
- built for polyolefin films



PRODUCTS ENGINEERED FOR  
**TOTAL FINISHING POWER**

Total Print Finishing Services  
Unit 4 Becks Business Park  
Warne Road  
Weston-Super-Mare BS23 3TS  
+44 (0)1934 645050  
sales@totalpfs.co.uk  
www.totalpfs.co.uk

Our **TPF 5000** represents the culmination of very considerable research and development effort to produce a seal and shrink unit, where every characteristic is optimised, with particular emphasis on the successful processing of polyolefin film. The fundamental design objectives are the lowest possible purchase and running costs, with the highest quality packs, wrapped in polyolefin material, produced at the fastest rate, from a unit which maximises user friendliness.

### The TPF 5000 offers the following significant advantages

- Suitable for tall, irregular, or multi packs
- Easy operation by a single person
- Particularly small space requirement
- Seal only, multiple or single seal/shrink
- Polyolefin and PVC processing
- Continuous or intermittent production
- Minimal installation and start up times
- Straight-forward control of all functions
- Fully adjustable multiple micro-perforators
- Stored heat functionality
- Solenoid clamp down in three modes
- Very low maintenance requirements
- Immediately available from stock
- Complete support with film and service

### TPF 5000 Specifications

Power requirements	220V 50 Hz
Power consumption (maximum) (Kw)	3
Power consumption (running) (Kw/h)	1.9
Sealing dimensions (a)	550 x 420
Maximum pack height (a)	250
Machine dimensions (l x w x h)	1230x750x1165
Maximum reel width	800
Approximate output (packs/hr) (b)	300



**PRODUCTS ENGINEERED FOR  
TOTAL FINISHING POWER**

Total Print Finishing Services  
Unit 4 Becks Business Park  
Warne Road  
Weston-Super-Mare BS23 3TS  
+44 (0)1934 645050  
sales@totalpfs.co.uk  
www.totalpfs.co.uk